Fixture INTER-PLUS -CC ZW


Ref. FPIP003



CRI 90+ | IP20 | CE | UKCA | RoHS COMPLIANT

- Complete luminaires for suspended mounting
- Includes constant current light source, mounting components, and electronics
- Possiblity to obtain UGR < 19
- High lighting efficacy
- Tool-free installation of the profile on an aluminum strip facilitates luminaire servicing

TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Material	**aluminum**
Mounting type	**Suspended**
Height H	**60 mm**
Width [W]	**49.9 mm**
Shape	**linear**
Lighting direction	**down**
IP protection rating	**20**
LxBy	**L90B10**
Lifetime	**100000 h**
Color Rendering Index CRI	**90**
Input voltage	**220-240 V 50/60 Hz**
Protection class	**I**

Color	Cover	Control	Length [L]	Luminous flux of the fixture	Luminare power	Efficiency	Color temperature	Ref
silver anodized	frosted	DALI	866 mm	2450 lm	19 W	129 lm/W	3000 K	**FPIP003-0130DB**
silver anodized	frosted	ON/OFF	866 mm	2450 lm	19 W	129 lm/W	3000 K	**FPIP003-0130EB**

Fixture INTER-PLUS -CC ZW

Ref. FPIP003

Color	Cover	Control	Length [L]	Luminous flux of the fixture	Luminare power	Efficiency	Color temperature	Ref
silver anodized	frosted	DALI	866 mm	2450 lm	19 W	129 lm/W	4000 K	**FPIP003-0140DB**
silver anodized	frosted	ON/OFF	866 mm	2450 lm	19 W	129 lm/W	4000 K	**FPIP003-0140EB**
black anodized	frosted	DALI	866 mm	2450 lm	19 W	129 lm/W	3000 K	**FPIP003-0730DB**
black anodized	frosted	ON/OFF	866 mm	2450 lm	19 W	129 lm/W	3000 K	**FPIP003-0730EB**
black anodized	frosted	DALI	866 mm	2450 lm	19 W	129 lm/W	4000 K	**FPIP003-0740DB**
black anodized	frosted	ON/OFF	866 mm	2450 lm	19 W	129 lm/W	4000 K	**FPIP003-0740EB**
white-matt lacquered	frosted	DALI	866 mm	2450 lm	19 W	129 lm/W	3000 K	**FPIP003-1030DB**
white-matt lacquered	frosted	ON/OFF	866 mm	2450 lm	19 W	129 lm/W	3000 K	**FPIP003-1030EB**
white-matt lacquered	frosted	DALI	866 mm	2450 lm	19 W	129 lm/W	4000 K	**FPIP003-1040DB**
white-matt lacquered	frosted	ON/OFF	866 mm	2450 lm	19 W	129 lm/W	4000 K	**FPIP003-1040EB**
silver anodized	frosted	DALI	1146 mm	3300 lm	25 W	132 lm/W	3000 K	**FPIP004-0130DB**
silver anodized	frosted	ON/OFF	1146 mm	3300 lm	25 W	132 lm/W	3000 K	**FPIP004-0130EB**
silver anodized	frosted	DALI	1146 mm	3300 lm	25 W	132 lm/W	4000 K	**FPIP004-0140DB**
silver anodized	frosted	ON/OFF	1146 mm	3300 lm	25 W	132 lm/W	4000 K	**FPIP004-0140EB**
black anodized	frosted	DALI	1146 mm	3300 lm	25 W	132 lm/W	3000 K	**FPIP004-0730DB**
black anodized	frosted	ON/OFF	1146 mm	3300 lm	25 W	132 lm/W	3000 K	**FPIP004-0730EB**
black anodized	frosted	DALI	1146 mm	3300 lm	25 W	132 lm/W	4000 K	**FPIP004-0740DB**
black anodized	frosted	ON/OFF	1146 mm	3300 lm	25 W	132 lm/W	4000 K	**FPIP004-0740EB**
white-matt lacquered	frosted	DALI	1146 mm	3300 lm	25 W	132 lm/W	3000 K	**FPIP004-1030DB**
white-matt lacquered	frosted	ON/OFF	1146 mm	3300 lm	25 W	132 lm/W	3000 K	**FPIP004-1030EB**
white-matt lacquered	frosted	DALI	1146 mm	3300 lm	25 W	132 lm/W	4000 K	**FPIP004-1040DB**
white-matt lacquered	frosted	ON/OFF	1146 mm	3300 lm	25 W	132 lm/W	4000 K	**FPIP004-1040EB**
silver anodized	frosted	DALI	1426 mm	4100 lm	31 W	132 lm/W	3000 K	**FPIP005-0130DB**
silver anodized	frosted	ON/OFF	1426 mm	4100 lm	31 W	132 lm/W	3000 K	**FPIP005-0130EB**
silver anodized	frosted	DALI	1426 mm	4100 lm	31 W	132 lm/W	4000 K	**FPIP005-0140DB**
silver anodized	frosted	ON/OFF	1426 mm	4100 lm	31 W	132 lm/W	4000 K	**FPIP005-0140EB**
black anodized	frosted	DALI	1426 mm	4100 lm	31 W	132 lm/W	3000 K	**FPIP005-0730DB**
black anodized	frosted	ON/OFF	1426 mm	4100 lm	31 W	132 lm/W	3000 K	**FPIP005-0730EB**
black anodized	frosted	DALI	1426 mm	4100 lm	31 W	132 lm/W	4000 K	**FPIP005-0740DB**
black anodized	frosted	ON/OFF	1426 mm	4100 lm	31 W	132 lm/W	4000 K	**FPIP005-0740EB**
white-matt lacquered	frosted	DALI	1426 mm	4100 lm	31 W	132 lm/W	3000 K	**FPIP005-1030DB**
white-matt lacquered	frosted	ON/OFF	1426 mm	4100 lm	31 W	132 lm/W	3000 K	**FPIP005-1030EB**
white-matt lacquered	frosted	DALI	1426 mm	4100 lm	31 W	132 lm/W	4000 K	**FPIP005-1040DB**
white-matt lacquered	frosted	ON/OFF	1426 mm	4100 lm	31 W	132 lm/W	4000 K	**FPIP005-1040EB**
silver anodized	frosted	DALI	1706 mm	4950 lm	37 W	134 lm/W	3000 K	**FPIP006-0130DB**
silver anodized	frosted	ON/OFF	1706 mm	4950 lm	37 W	134 lm/W	3000 K	**FPIP006-0130EB**
silver anodized	frosted	DALI	1706 mm	4950 lm	37 W	134 lm/W	4000 K	**FPIP006-0140DB**
silver anodized	frosted	ON/OFF	1706 mm	4950 lm	37 W	134 lm/W	4000 K	**FPIP006-0140EB**
black anodized	frosted	DALI	1706 mm	4950 lm	37 W	134 lm/W	3000 K	**FPIP006-0730DB**
black anodized	frosted	ON/OFF	1706 mm	4950 lm	37 W	134 lm/W	3000 K	**FPIP006-0730EB**
black anodized	frosted	DALI	1706 mm	4950 lm	37 W	134 lm/W	4000 K	**FPIP006-0740DB**
black anodized	frosted	ON/OFF	1706 mm	4950 lm	37 W	134 lm/W	4000 K	**FPIP006-0740EB**
white-matt lacquered	frosted	DALI	1706 mm	4950 lm	37 W	134 lm/W	3000 K	**FPIP006-1030DB**
white-matt lacquered	frosted	ON/OFF	1706 mm	4950 lm	37 W	134 lm/W	3000 K	**FPIP006-1030EB**
white-matt lacquered	frosted	DALI	1706 mm	4950 lm	37 W	134 lm/W	4000 K	**FPIP006-1040DB**
white-matt lacquered	frosted	ON/OFF	1706 mm	4950 lm	37 W	134 lm/W	4000 K	**FPIP006-1040EB**
silver anodized	frosted	DALI	1986 mm	5750 lm	43 W	134 lm/W	3000 K	**FPIP007-0130DB**

Fixture INTER-PLUS -CC ZW

Ref. FPIP003

Color	Cover	Control	Length [L]	Luminous flux of the fixture	Luminare power	Efficiency	Color temperature	Ref
silver anodized	frosted	ON/OFF	1986 mm	5750 lm	43 W	134 lm/W	3000 K	**FPIP007-0130EB**
silver anodized	frosted	DALI	1986 mm	5750 lm	43 W	134 lm/W	4000 K	**FPIP007-0140DB**
silver anodized	frosted	ON/OFF	1986 mm	5750 lm	43 W	134 lm/W	4000 K	**FPIP007-0140EB**
black anodized	frosted	DALI	1986 mm	5750 lm	43 W	134 lm/W	3000 K	**FPIP007-0730DB**
black anodized	frosted	ON/OFF	1986 mm	5750 lm	43 W	134 lm/W	3000 K	**FPIP007-0730EB**
black anodized	frosted	DALI	1986 mm	5750 lm	43 W	134 lm/W	4000 K	**FPIP007-0740DB**
black anodized	frosted	ON/OFF	1986 mm	5750 lm	43 W	134 lm/W	4000 K	**FPIP007-0740EB**
white-matt lacquered	frosted	DALI	1986 mm	5750 lm	43 W	134 lm/W	3000 K	**FPIP007-1030DB**
white-matt lacquered	frosted	ON/OFF	1986 mm	5750 lm	43 W	134 lm/W	3000 K	**FPIP007-1030EB**
white-matt lacquered	frosted	DALI	1986 mm	5750 lm	43 W	134 lm/W	4000 K	**FPIP007-1040DB**
white-matt lacquered	frosted	ON/OFF	1986 mm	5750 lm	43 W	134 lm/W	4000 K	**FPIP007-1040EB**
silver anodized	microprism	DALI	866 mm	2600 lm	19 W	137 lm/W	3000 K	**FPIP103-0130DB**
silver anodized	microprism	ON/OFF	866 mm	2600 lm	19 W	137 lm/W	3000 K	**FPIP103-0130EB**
silver anodized	microprism	DALI	866 mm	2600 lm	19 W	137 lm/W	4000 K	**FPIP103-0140DB**
silver anodized	microprism	ON/OFF	866 mm	2600 lm	19 W	137 lm/W	4000 K	**FPIP103-0140EB**
black anodized	microprism	DALI	866 mm	2600 lm	19 W	137 lm/W	3000 K	**FPIP103-0730DB**
black anodized	microprism	ON/OFF	866 mm	2600 lm	19 W	137 lm/W	3000 K	**FPIP103-0730EB**
black anodized	microprism	DALI	866 mm	2600 lm	19 W	137 lm/W	4000 K	**FPIP103-0740DB**
black anodized	microprism	ON/OFF	866 mm	2600 lm	19 W	137 lm/W	4000 K	**FPIP103-0740EB**
white-matt lacquered	microprism	DALI	866 mm	2600 lm	19 W	137 lm/W	3000 K	**FPIP103-1030DB**
white-matt lacquered	microprism	ON/OFF	866 mm	2600 lm	19 W	137 lm/W	3000 K	**FPIP103-1030EB**
white-matt lacquered	microprism	DALI	866 mm	2600 lm	19 W	137 lm/W	4000 K	**FPIP103-1040DB**
white-matt lacquered	microprism	ON/OFF	866 mm	2600 lm	19 W	137 lm/W	4000 K	**FPIP103-1040EB**
silver anodized	microprism	DALI	1146 mm	3450 lm	25 W	138 lm/W	3000 K	**FPIP104-0130DB**
silver anodized	microprism	ON/OFF	1146 mm	3450 lm	25 W	138 lm/W	3000 K	**FPIP104-0130EB**
silver anodized	microprism	DALI	1146 mm	3450 lm	25 W	138 lm/W	4000 K	**FPIP104-0140DB**
silver anodized	microprism	ON/OFF	1146 mm	3450 lm	25 W	138 lm/W	4000 K	**FPIP104-0140EB**
black anodized	microprism	DALI	1146 mm	3450 lm	25 W	138 lm/W	3000 K	**FPIP104-0730DB**
black anodized	microprism	ON/OFF	1146 mm	3450 lm	25 W	138 lm/W	3000 K	**FPIP104-0730EB**
black anodized	microprism	DALI	1146 mm	3450 lm	25 W	138 lm/W	4000 K	**FPIP104-0740DB**
black anodized	microprism	ON/OFF	1146 mm	3450 lm	25 W	138 lm/W	4000 K	**FPIP104-0740EB**
white-matt lacquered	microprism	DALI	1146 mm	3450 lm	25 W	138 lm/W	3000 K	**FPIP104-1030DB**
white-matt lacquered	microprism	ON/OFF	1146 mm	3450 lm	25 W	138 lm/W	3000 K	**FPIP104-1030EB**
white-matt lacquered	microprism	DALI	1146 mm	3450 lm	25 W	138 lm/W	4000 K	**FPIP104-1040DB**
white-matt lacquered	microprism	ON/OFF	1146 mm	3450 lm	25 W	138 lm/W	4000 K	**FPIP104-1040EB**
silver anodized	microprism	DALI	1426 mm	4300 lm	31 W	139 lm/W	3000 K	**FPIP105-0130DB**
silver anodized	microprism	ON/OFF	1426 mm	4300 lm	31 W	139 lm/W	3000 K	**FPIP105-0130EB**
silver anodized	microprism	DALI	1426 mm	4300 lm	31 W	139 lm/W	4000 K	**FPIP105-0140DB**
silver anodized	microprism	ON/OFF	1426 mm	4300 lm	31 W	139 lm/W	4000 K	**FPIP105-0140EB**
black anodized	microprism	DALI	1426 mm	4300 lm	31 W	139 lm/W	3000 K	**FPIP105-0730DB**
black anodized	microprism	ON/OFF	1426 mm	4300 lm	31 W	139 lm/W	3000 K	**FPIP105-0730EB**
black anodized	microprism	DALI	1426 mm	4300 lm	31 W	139 lm/W	4000 K	**FPIP105-0740DB**
black anodized	microprism	ON/OFF	1426 mm	4300 lm	31 W	139 lm/W	4000 K	**FPIP105-0740EB**
white-matt lacquered	microprism	DALI	1426 mm	4300 lm	31 W	139 lm/W	3000 K	**FPIP105-1030DB**
white-matt lacquered	microprism	ON/OFF	1426 mm	4300 lm	31 W	139 lm/W	3000 K	**FPIP105-1030EB**
white-matt lacquered	microprism	DALI	1426 mm	4300 lm	31 W	139 lm/W	4000 K	**FPIP105-1040DB**
white-matt lacquered	microprism	ON/OFF	1426 mm	4300 lm	31 W	139 lm/W	4000 K	**FPIP105-1040EB**

Fixture INTER-PLUS -CC ZW

Ref. FPIP003

Color	Cover	Control	Length [L]	Luminous flux of the fixture	Luminare power	Efficiency	Color temperature	Ref
silver anodized	microprism	DALI	1706 mm	5150 lm	37 W	139 lm/W	3000 K	**FPIP106-0130DB**
silver anodized	microprism	ON/OFF	1706 mm	5150 lm	37 W	139 lm/W	3000 K	**FPIP106-0130EB**
silver anodized	microprism	DALI	1706 mm	5150 lm	37 W	139 lm/W	4000 K	**FPIP106-0140DB**
silver anodized	microprism	ON/OFF	1706 mm	5150 lm	37 W	139 lm/W	4000 K	**FPIP106-0140EB**
black anodized	microprism	DALI	1706 mm	5150 lm	37 W	139 lm/W	3000 K	**FPIP106-0730DB**
black anodized	microprism	ON/OFF	1706 mm	5150 lm	37 W	139 lm/W	3000 K	**FPIP106-0730EB**
black anodized	microprism	DALI	1706 mm	5150 lm	37 W	139 lm/W	4000 K	**FPIP106-0740DB**
black anodized	microprism	ON/OFF	1706 mm	5150 lm	37 W	139 lm/W	4000 K	**FPIP106-0740EB**
white-matt lacquered	microprism	DALI	1706 mm	5150 lm	37 W	139 lm/W	3000 K	**FPIP106-1030DB**
white-matt lacquered	microprism	ON/OFF	1706 mm	5150 lm	37 W	139 lm/W	3000 K	**FPIP106-1030EB**
white-matt lacquered	microprism	DALI	1706 mm	5150 lm	37 W	139 lm/W	4000 K	**FPIP106-1040DB**
white-matt lacquered	microprism	ON/OFF	1706 mm	5150 lm	37 W	139 lm/W	4000 K	**FPIP106-1040EB**
silver anodized	microprism	DALI	1986 mm	6000 lm	43 W	140 lm/W	3000 K	**FPIP107-0130DB**
silver anodized	microprism	ON/OFF	1986 mm	6000 lm	43 W	140 lm/W	3000 K	**FPIP107-0130EB**
silver anodized	microprism	DALI	1986 mm	6000 lm	43 W	140 lm/W	4000 K	**FPIP107-0140DB**
silver anodized	microprism	ON/OFF	1986 mm	6000 lm	43 W	140 lm/W	4000 K	**FPIP107-0140EB**
black anodized	microprism	DALI	1986 mm	6000 lm	43 W	140 lm/W	3000 K	**FPIP107-0730DB**
black anodized	microprism	ON/OFF	1986 mm	6000 lm	43 W	140 lm/W	3000 K	**FPIP107-0730EB**
black anodized	microprism	DALI	1986 mm	6000 lm	43 W	140 lm/W	4000 K	**FPIP107-0740DB**
black anodized	microprism	ON/OFF	1986 mm	6000 lm	43 W	140 lm/W	4000 K	**FPIP107-0740EB**
white-matt lacquered	microprism	DALI	1986 mm	6000 lm	43 W	140 lm/W	3000 K	**FPIP107-1030DB**
white-matt lacquered	microprism	ON/OFF	1986 mm	6000 lm	43 W	140 lm/W	3000 K	**FPIP107-1030EB**
white-matt lacquered	microprism	DALI	1986 mm	6000 lm	43 W	140 lm/W	4000 K	**FPIP107-1040DB**
white-matt lacquered	microprism	ON/OFF	1986 mm	6000 lm	43 W	140 lm/W	4000 K	**FPIP107-1040EB**

SAMPLE PROJECTS

