
Extrusion KOZMA-22-BOK

Ref. A00018



KEY FEATURES

- Dedicated for finishing built-in structures made of plasterboard
- Mounting to 12,5 mm - 0.50" drywall
- Compact dimensions – no collision with ceiling structure

APPLICATION

main and decorative lighting

MOUNTING

in drywall, with mounting adhesive

ADDITIONAL INFORMATION

- in order to protect the lighting fixture during installation, a TECH-KA protective insert should be used
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ


IP PROTECTION RATING

IP20 | IP65

MOUNTING METHOD

Trimless

TECHNICAL DRAWING



AVAILABLE COLOURS

COLOR	LENGTH	REF
silver anodized	39.4"	A00018A_1
	78.9"	A00018A_2
	118.5"	A00018A_3
silver non anodized	39.4"	A00018N_1
	78.9"	A00018N_2
	118.5"	A00018N_3

TECHNICAL SPECIFICATIONS

Material	aluminum
Possible fixture IP	20, 65
Possible fixture shapes	linear, polygonal
Profile cross-section	rectangular
Width	1.8"
Height	0.6"
Maximum length on request	0.2"
LED gluing width A	0.9"
Max. number of LED strips A (0.31" wide)	2
Width of the glow	22 mm
Max power of a single KLUŚ LED strip	5.9 W/ft
Building type	Commercial, Residential, Hotel / Restaurant, Retail, Entertainment/ Arts
The cover is cut to the length of the profile	yes
Can be easily connected into runs	yes
Mounting to drywall	yes
To cover with plaster	yes
Wire out back of extrusion	yes

RELATED ACCESSORIES > COVERS

NAME	KEY FEATURES	MATERIAL	MATERIAL TRANSMITTANCE	COLOR	REF.
G-22R Cover	- indoor use - perfectly diffusing	PMMA	20 %	black	B17006B
			71 %	satin	B17006S
			89 %	semi-transparent	B17006T
			94 %	clear	B17006C
HS-22 Cover	- For indoor and outdoor applications - UV resistant	PC	65 %	frosted	B17011F
			88 %	clear	B17011C
			90.5 %	microprism	B17011M
G-22S Cover	- indoor use - perfectly diffusing	PMMA	15 %	black	B17013B
			86 %	satin	B17013S
			89 %	semi-transparent	B17013T

Extrusion KOZMA-22-BOK
Ref. A00018

NAME	KEY FEATURES	MATERIAL	MATERIAL TRANSMITTANCE	COLOR	REF.
LIGER-22 Cover	- hight light quality - For indoor and outdoor applications - Ease of obtaining a line of light - perfectly diffusing	PC	22 %	black	B17032B
			70 %	satin	B17032S
BENCO-22 Cover	- For indoor and outdoor applications - UV resistant	Silikon	62 %	frosted	B17209F

RELATED ACCESSORIES > END CAPS

NAME	MATERIAL	COLOR	REF.
GIZA-LL End cap 	ABS	black	C24281C07
		gray	C24281C02
		white	C24281C10
KOMPENSA-K End cap 	PP	black	C24020C07
		gray	C24020C02
KOMPENSA-L End cap 	PP	black	C24015C07
		gray	C24015C02

RELATED ACCESSORIES > OTHER ACCESSORIES > CONNECTORS

NAME	KEY FEATURES	MATERIAL	COLOR	REF.
ZM Connector		stainless steel	silver	42720 42728 C28070N00 C28071N00 C28072N00 C28073N00 C28074N00 C28075N00 C28243N00
ZM-NA Connector		stainless steel	silver	42339
ZM-NA-PION Connector		stainless steel	silver	42315 42317 42321
ZM-PION Connector	- for connecting profiles in the vertical plane	stainless steel	silver	42314 42316 42320 42718 42719 C28084N00 C28085N00 C28086N00 C28087N00 C28088N00

RELATED ACCESSORIES > RELATED LED > CRI 90+

NAME	KEY FEATURES	IP PROTECTION RATING	POWER CONSUMPTION	REF.
K-2400-24 LED tape	- high power	20	7.3 W/ft	K-27-2400-24 K-30-2400-24 K-35-2400-24 K-40-2400-24 K-50-2400-24