PIKO-KW Extrusion

Ref. A00035

NEW



KEY FEATURES

- Aesthetic decoration of internal corners with a thin line of light
- The profile flange masks the edges of slabs and tiles
- Installation on slabs and tiles with a maximum thickness of 13mm
- Wide range of accessories
- Possibility of installing sealed 5K series LED strips

APPLICATION

decorative lighting for internal corners

MOUNTING

in drywall, with mounting adhesive

IP PROTECTION RATING

IP20 IP65

MOUNTING METHOD

Recessed

TECHNICAL DRAWING



AVAILABLE COLOURS

COLOR	LENGTH	REF
black anodized	39.4"	A00035A07_1
	78.9"	A00035A07_2
silver anodized	39.4"	A00035A_1
	78.9"	A00035A_2
white lacquered	39.4"	A00035L10_1
	78.9"	A00035L10_2

TECHNICAL SPECIFICATIONS

Material	aluminum
Possible fixture IP	20, 65
Possible fixture shapes	linear
Profile cross-section	angled
Width	1.9"
Height	0.5"
LED gluing width A	0.3"
Width of the glow	7.2 mm
Max power of a single KLUŚ LED strip	2.9 W/ft
Building type	Residential, Hotel / Restaurant, Entertainment/ Arts
Facility zone	communication routes and corridors, decorative, bathroom, edge lighting
The cover is cut to the length of the profile	yes
Decorative lighting	yes
Mounting to drywall	yes

RELATED ACCESSORIES > COVERS

NAME	KEY FEATURES	MATERIAL	MATERIAL TRANSMITTANCE	COLOR	REF.
PIKO-7 Cover	- For indoor and outdoor applications - perfectly diffusing - UV resistant - Thin line of light	PMMA	17 %	black	B17001B
			43 %	satin	B17001S
PIKO-7R Cover	- indoor use - perfectly diffusing - Thin line of light	PMMA	24 %	black	B17164B
			52 %	satin	B17164S

RELATED ACCESSORIES > END CAPS

NAME		MATERIAL	COLOR	REF.
PIKO-KW End cap	NEW	ASA	black	C24780C07
			silver	C24780C02
			white	C24780C10

PIKO-KW Extrusion

Ref. A00035

NAME			MATERIAL	COLOR	REF.
PIKO-KW-R End cap	NEW		ASA	black	C24781C07
				silver	C24781C02
				white	C24781C10

RELATED ACCESSORIES > RELATED LED > CRI 90+

NAME	KEY FEATURES	IP PROTECTION RATING	POWER CONSUMPTION	REF.
K-SHD-0960-24 LED tape	- ideal for use with black covers - high LED density	20	2.9 W/ft	K-SHD22-0960-24 K-SHD25-0960-24 K-SHD27-0960-24 K-SHD30-0960-24 K-SHD35-0960-24 K-SHD40-0960-24 K-SHD50-0960-24