PDS-T Extrusion

Ref. A02057



KEY FEATURES

- Mounting to 12,5 mm - 0.50" drywall
- No collision with the ceiling structure
- Stable mounting to a suspended ceiling
- Non visible aluminum elements

APPLICATION

main and decorative lighting

MOUNTING

in drywall, with screws

ADDITIONAL INFORMATION

- smooth transition from a recessed into a suspended fixture
- in order to protect the lighting fixture during installation, a TECH-KA protective insert should be used
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

IP PROTECTION RATING

IP20 | IP67

MOUNTING METHOD

Trimless

TECHNICAL DRAWING



AVAILABLE COLOURS

LENGTH	REF
39.4"	A02057N_1
78.9"	A02057N_2

TECHNICAL SPECIFICATIONS

Material	aluminum
Color	silver non anodized
Possible fixture IP	20, 67
Possible fixture shapes	linear, polygonal
Profile cross-section	rectangular
Width	2.1"
Height	0.6"
LED gluing width A	0.6"
Max. number of LED strips A (0.31" wide)	1
Width of the glow	11.2 mm
Max power of a single KLUŚ LED strip	7.3 W/ft
Possibility of obtaining a line of light	yes
Building type	Commercial, Hotel / Restaurant, Retail, Residential, Entertainment/ Arts, Outdoor
Facility zone	office, lobby / foyer, media rooms / av
The cover is cut to the length of the profile	yes
Can be easily connected into runs	yes
Mounting to drywall	yes
To cover with plaster	yes
Wire out back of extrusion	yes

RELATED ACCESSORIES > COVERS

NAME	KEY FEATURES	MATERIAL	MATERIAL TRANSMITTANCE	COLOR	REF.
LIGER-11 Cover	- hight light quality - Ease of obtaining a line of light - perfectly diffusing - For indoor and outdoor applications	PC	21 %	black	B17037B
			59 %	satin	B17037S
HS-11 Cover	- For indoor and outdoor applications - UV resistant - hight durability	PC	59 %	frosted	B17208F
			88 %	clear	B17208C
LENSO-11 30°DEG Focusing cover	- indoor use - focusing	PC	80 %	semi-transparent	B17112T
KA-11 Cover	- maximum brightness - indoor use - basic - universal	PC	67 %	frosted	B17064F
			89 %	clear	B17064C

PDS-T Extrusion
Ref. A02057

LINE OF LIGHT TABLE

LED TAPE	LIGER-11 SATIN	LIGER-11 BLACK	HS-11 FROSTED	KA-11 FROSTED
K-0360-24	✓ (1)	X	✓ (1)	✓ (1)
K-0720-24	✓ (1)	X	✓ (1)	✓ (1)
K-1080-24	✓ (1)	X	✓ (1)	✓ (1)
K-HD-0430-24	✓ (1)	✓ (1)	✓ (1)	✓ (1)
K-HD-0830-24	✓ (1)	✓ (1)	✓ (1)	✓ (1)
K-HD-1260-24	✓ (1)	✓ (1)	✓ (1)	✓ (1)
KWP-8K-0360-24	✓ (1)	X	✓ (1)	✓ (1)
KWP-8K-0720-24	✓ (1)	X	✓ (1)	✓ (1)
KWP-8K-1080-24	✓ (1)	X	✓ (1)	✓ (1)
KWP-GHD-0430-24	✓ (1)	✓ (1)	✓ (1)	✓ (1)
KWP-GHD-0830-24	✓ (1)	✓ (1)	✓ (1)	✓ (1)
KWP-GHD-1260-24	✓ (1)	✓ (1)	✓ (1)	✓ (1)
K-CR-1220-24	✓ (1)	X	X	✓ (1)
K-CR-1275-24	✓ (1)	X	X	✓ (1)
K-CRHD-1820-24	✓ (1)	✓ (1)	✓ (1)	✓ (1)
K-CRHD-1910-24	✓ (1)	✓ (1)	✓ (1)	✓ (1)
K-HEHD-0480-24	✓ (1)	X	✓ (1)	✓ (1)
K-HEHD-0960-24	✓ (1)	X	✓ (1)	✓ (1)
K-HEHD-1440-24	✓ (1)	X	✓ (1)	✓ (1)
K-HEHD-1920-24	✓ (1)	X	✓ (1)	✓ (1)
K-HEHD-0320-24	✓ (1)	X	✓ (1)	✓ (1)
K-RGBW-1920-120-24	✓ (1)	X	X	✓ (1)
K-RGB-1200-24	✓ (1)	X	X	✓ (1)
K-RGB-0700-24V	✓ (1)	X	X	✓ (1)
K-2400-24	✓ (1)	X	✓ (1)	✓ (1)
K-SD-1440-24	✓ (1)	X	✓ (1)	✓ (1)
K-RGBW-1920-160-24	✓ (1)	X	✓ (1)	✓ (1)
KWP-GRGBW-1920-120-24	✓ (1)	X	X	✓ (1)
K-SDCR-22T50-1530-24	✓ (1)	✓ (1)	✓ (1)	✓ (1)
KWP-SDCR-22T50-1530-24	✓ (1)	✓ (1)	✓ (1)	✓ (1)

Description

✓ - Line of Light for a number (X) of rows - Pixel free imaging
X - Visible Dotting from Diodes
HL - Centered Line of Light - Concentrated in middle
HL (X) - Centered Line of Light for a number (X) of rows - Concentrated in middle

Line of Light Guide



Clean Line of Light (Pixel free imaging)



Centered Line of Light



Visible Dotting from Diodes

RELATED ACCESSORIES > END CAPS

NAME		MATERIAL	COLOR	REF.
PDS-ZM-PLUS End cap		ABS	black	C24364C07
			gray	C24364C02
			silver	C24364L01
			white	C24364C10

RELATED ACCESSORIES > OTHER ACCESSORIES > CONNECTORS

NAME	KEY FEATURES	MATERIAL	COLOR	REF.
ZM Connector		stainless steel	silver	42720 42728 C28070N00 C28071N00 C28072N00 C28073N00 C28074N00 C28075N00 C28243N00
ZM-NA Connector		stainless steel	silver	42339

PDS-T Extrusion
Ref. A02057

NAME	KEY FEATURES	MATERIAL	COLOR	REF.
ZM-PION Connector	- for connecting profiles in the vertical plane	stainless steel	silver	42314 42316 42320 42718 42719 C28084N00 C28085N00 C28086N00 C28087N00 C28088N00
ZM-NA-PION Connector		stainless steel	silver	42315 42317 42321

RELATED ACCESSORIES > RELATED LED > HIGH EFFICACY

NAME	KEY FEATURES	IP PROTECTION RATING	POWER CONSUMPTION	REF.
K-HEHD-0320-24 LED tape	- CRI over 95 - High Efficacy	20	1 W/ft	K-HEHD27-0320-24 K-HEHD30-0320-24 K-HEHD35-0320-24 K-HEHD40-0320-24
K-HEHD-0480-24 LED tape	- CRI over 95 - High Efficacy	20	1.5 W/ft	K-HEHD22-0480-24 K-HEHD25-0480-24 K-HEHD27-0480-24 K-HEHD30-0480-24 K-HEHD35-0480-24 K-HEHD40-0480-24 K-HEHD50-0480-24
K-HEHD-0960-24 LED tape	- CRI over 95 - High Efficacy	20	2.9 W/ft	K-HEHD22-0960-24 K-HEHD25-0960-24 K-HEHD27-0960-24 K-HEHD30-0960-24 K-HEHD35-0960-24 K-HEHD40-0960-24 K-HEHD50-0960-24
K-HEHD-1440-24 LED tape	- CRI over 95 - High Efficacy	20	4.4 W/ft	K-HEHD22-1440-24 K-HEHD25-1440-24 K-HEHD27-1440-24 K-HEHD30-1440-24 K-HEHD35-1440-24 K-HEHD40-1440-24 K-HEHD50-1440-24
LED tape K-HEHD-1920-24	- CRI over 95 - High Efficacy	20	5.9 W/ft	K-HEHD22-1920-24 K-HEHD25-1920-24 K-HEHD27-1920-24 K-HEHD30-1920-24 K-HEHD35-1920-24 K-HEHD40-1920-24 K-HEHD50-1920-24

RELATED ACCESSORIES > RELATED LED > CRI 95+

NAME	KEY FEATURES	IP PROTECTION RATING	POWER CONSUMPTION	REF.
K-CR-1210-24 LED tape	- CRI over 95	20	1.5 W/ft	K-CR22-1210-24 K-CR27-1210-24
K-CRHD-1910-24 LED tape	- CRI over 95 - high LED density	20	2.8 W/ft	K-CRHD27-1910-24 K-CRHD35-1910-24 K-CRHD40-1910-24
K-CR-1220-24 LED tape	- CRI over 95	20	2.9 W/ft	K-CR22-1220-24 K-CR25-1220-24 K-CR27-1220-24 K-CR30-1220-24 K-CR35-1220-24 K-CR40-1220-24 K-CR50-1220-24
K-CR-1275-24 LED tape	- CRI over 95	20	4.4 W/ft	K-CR22-1275-24 K-CR25-1275-24 K-CR27-1275-24 K-CR30-1275-24 K-CR35-1275-24 K-CR40-1275-24 K-CR50-1275-24
K-CRHD-1820-24 LED tape	- CRI over 95 - high LED density	20	5.6 W/ft	K-CRHD27-1820-24

RELATED ACCESSORIES > RELATED LED > CRI 90+

NAME	KEY FEATURES	IP PROTECTION RATING	POWER CONSUMPTION	REF.
K-2400-24 LED tape	- high power	20	7.3 W/ft	K-27-2400-24 K-30-2400-24 K-35-2400-24 K-40-2400-24 K-50-2400-24

PDS-T Extrusion
Ref. A02057

NAME	KEY FEATURES	IP PROTECTION RATING	POWER CONSUMPTION	REF.
LED tape KWP-8K-1275-24	- easy snap-in installation	65	4.4 W/ft	KWP-8K22-1275-24 KWP-8K25-1275-24 KWP-8K27-1275-24 KWP-8K30-1275-24 KWP-8K35-1275-24 KWP-8K40-1275-24 KWP-8K50-1275-24

RELATED ACCESSORIES > RELATED LED > ADJUSTABLE WHITE / DIM TO WARM

NAME	KEY FEATURES	IP PROTECTION RATING	POWER CONSUMPTION	REF.
K-SDCR-22T50-1530-24 LED tape	- Tuneable white 2200K-5000K	20	4.7 W/ft	K-SDCR-22T50-1530-24
KWP-SDCR-22T50-1530-24 LED tape	- Tuneable white 2200K-5000K	65	4.7 W/ft	KWP-SDCR-22T50-1530-24

RELATED ACCESSORIES > ELECTRONICS > SWITCHES

NAME	KEY FEATURES	IP PROTECTION RATING	REF.
Switch MICRO 96W IP20	- push button switch - factory pre-soldered wires	20	1576
Proximity switch UNI	- touchless switch - width only 7mm	20	E61579