TAMI Extrusion
Ref. A05390



KEY FEATURES

- Simplified design
- Minimum height

APPLICATION

furniture and functional lighting

MOUNTING

to the surface or recessed, using dedicated accessories, properly selected screws, with double-sided adhesive tape or mounting adhesive
easy assembly and disassembly by snapping in and out

ADDITIONAL INFORMATION

- cover with a simplified structure
- not recommended to be used with LEDs exceeding 4.5w/ft
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ


IP PROTECTION RATING

IP20

MOUNTING METHOD

Surface mounted

TECHNICAL DRAWING



AVAILABLE COLOURS

COLOR	LENGTH	REF
silver non anodized	39.4"	A05390N_1
	78.9"	A05390N_2
silver anodized	39.4"	A05390A_1
	78.9"	A05390A_2

TECHNICAL SPECIFICATIONS

Material	aluminum
Possible fixture IP	20
Possible fixture shapes	linear, polygonal
Profile cross-section	rectangular
Width	0.6"
Height	0.3"
LED gluing width A	0.5"
Max. number of LED strips A (0.31" wide)	1
Width of the glow	12.5 mm
Max power of a single KLUŚ LED strip	4.6 W/ft
Building type	Residential, Retail, Hotel / Restaurant
Facility zone	kitchen, bathroom, under-cabinet / furniture, exhibition / tradeshow / display
Easy assembly and disassembly by snapping in and out	yes
The cover is cut to the length of the profile	yes
Wire out end cap	yes
Wire out back of extrusion	yes

RELATED ACCESSORIES > COVERS

NAME	KEY FEATURES	MATERIAL	MATERIAL TRANSMITTANCE	COLOR	REF.
T-13 Cover	- indoor use - for basic applications	PMMA	85 %	semi-transparent	B17015T

RELATED ACCESSORIES > END CAPS

NAME	MATERIAL	COLOR	REF.
TAMI EKO End cap	PP	white	C20051C10

TAMI Extrusion
Ref. A05390

RELATED ACCESSORIES > PROFILE TECHNICZNE

NAME	MATERIAL	COLOR	REF.
TEST-36 Extrusion	aluminum	silver anodized	A06639

RELATED ACCESSORIES > OTHER ACCESSORIES > CANOPIES

NAME	KEY FEATURES	MATERIAL	COLOR	REF.
Fi-60mm Canopy	- Convenient cable length adjustment, in the ZM system	steel	gray lacquered white lacquered black lacquered	C24540L01 C24540L10 C24540L07

RELATED ACCESSORIES > OTHER ACCESSORIES > MOUNTING BRACKETS

NAME	KEY FEATURES	MATERIAL	COLOR	REF.
REG-PD-EXT Mounting bracket NEW	- Mounting with angle adjustment function	aluminum, stainless steel	black white gray	C28303C07 C28303C10 C28303N00
PDS-STN Mounting bracket	- For indoor and outdoor applications	stainless steel	silver	C24190N00
PDS Mounting bracket	- For indoor and outdoor applications	stainless steel	white black	C24223C10 C24189C07
PDS-STN-90G Mounting bracket	- Angular mount for indoor and outdoor applications	stainless steel	silver white black	C24370N00 C24370L10 C24370L07
PDS-STN-90D Mounting bracket	- Angular mount for indoor and outdoor applications	stainless steel	silver white black	C24367N00 C24367L10 C24367L07

RELATED ACCESSORIES > OTHER ACCESSORIES > FASTENERS AND HEADS FOR EXTRUSIONS

NAME	MATERIAL	COLOR	REF.
ST Head	stainless steel	silver	C28114N00
BZP Head	stainless steel	silver	C28113N00
DP-MOC Fastener , silver	stainless steel	silver	00645

RELATED ACCESSORIES > OTHER ACCESSORIES > CONDUCTIVE FASTENERS AND HEADS FOR EXTRUSIONS

NAME	KEY FEATURES	MATERIAL	COLOR	REF.
ZZ Head		stainless steel	silver	42218
BZP-ZZ Head		stainless steel	gray	42215
PUSZ-LIN-MR Fastener	- Power supply cable - mounting in thin walls (from 1mm)	stainless steel, brass, nylon aluminum, brass, nylon aluminum, brass, nylon	silver white lacquered black lacquered	C28163N00 C28163L10 C28163L07
FI-8-LIN-MR Fastener	- Power supply cable - mounting in thin walls (from 1mm)	stainless steel, PA aluminum, PA aluminum, PA	silver white black	C28172N00 C28172L10 C28172L07
Fastener PUSZ-MR	- Power supply cable - mounting in thin walls (from 1mm)	stainless steel aluminum aluminum	silver white lacquered black lacquered	C20011N00 C20011L10 C20011L07

RELATED ACCESSORIES > OTHER ACCESSORIES > CONNECTORS

NAME	MATERIAL	COLOR	REF.
Connector PD-MICRO	stainless steel	silver	C42150N00

RELATED ACCESSORIES > OTHER ACCESSORIES > SUSPENSION AND MOUNTING SETS

NAME	KEY FEATURES	MATERIAL	COLOR	REF.
Fastener set M3		stainless steel	silver	C28182N00
Fastener set M4		stainless steel	silver	C28180N00
Fastener set M5		stainless steel	silver	C28181N00
M14 Fastener set		stainless steel	silver	42612
RG-1 Fastener set	- Cable adjustment at the ceiling, cable included	brass	silver glossy black colored	C28230P00 C28230L07
Fastener set PUSZ-MR-1	- Power supply, for wall and drywall, mounting in thin walls (from 1mm)	stainless steel, aluminum	silver white lacquered black lacquered	C28132N00 C28132L10 C28132L07
Fastener set PUSZ-MR-2	- Convenient cable length adjustment, mounting in thin walls (from 1mm)	stainless steel, aluminum	silver white lacquered black lacquered	C28133N00 C28133L10 C28133L07
Fastener set FI-8-MR-1	- Power supply, for wall and drywall, mounting in thin walls (from 1mm)	stainless steel, aluminum	silver white lacquered black lacquered	C28136N00 C28136L10 C28136L07
Fastener set FI-8-MR-2	- Convenient cable length adjustment, mounting in thin walls (from 1mm)	stainless steel, aluminum	silver white lacquered black lacquered	C28137N00 C28137L10 C28137L07

TAMI Extrusion
Ref. A05390

RELATED ACCESSORIES > RELATED LED > HIGH EFFICACY

NAME	KEY FEATURES	IP PROTECTION RATING	POWER CONSUMPTION	REF.
K-HEHD-0320-24 LED tape	- CRI over 95 - High Efficacy	20	1 W/ft	K-HEHD27-0320-24 K-HEHD30-0320-24 K-HEHD35-0320-24 K-HEHD40-0320-24
K-HEHD-0480-24 LED tape	- CRI over 95 - High Efficacy	20	1.5 W/ft	K-HEHD22-0480-24 K-HEHD25-0480-24 K-HEHD27-0480-24 K-HEHD30-0480-24 K-HEHD35-0480-24 K-HEHD40-0480-24 K-HEHD50-0480-24
K-HEHD-0960-24 LED tape	- CRI over 95 - High Efficacy	20	2.9 W/ft	K-HEHD22-0960-24 K-HEHD25-0960-24 K-HEHD27-0960-24 K-HEHD30-0960-24 K-HEHD35-0960-24 K-HEHD40-0960-24 K-HEHD50-0960-24
K-HEHD-1440-24 LED tape	- CRI over 95 - High Efficacy	20	4.4 W/ft	K-HEHD22-1440-24 K-HEHD25-1440-24 K-HEHD27-1440-24 K-HEHD30-1440-24 K-HEHD35-1440-24 K-HEHD40-1440-24 K-HEHD50-1440-24
LED tape K-HEHD-1920-24	- CRI over 95 - High Efficacy	20	5.9 W/ft	K-HEHD22-1920-24 K-HEHD25-1920-24 K-HEHD27-1920-24 K-HEHD30-1920-24 K-HEHD35-1920-24 K-HEHD40-1920-24 K-HEHD50-1920-24

RELATED ACCESSORIES > RELATED LED > CRI 95+

NAME	KEY FEATURES	IP PROTECTION RATING	POWER CONSUMPTION	REF.
K-CR-1210-24 LED tape	- CRI over 95	20	1.5 W/ft	K-CR22-1210-24 K-CR27-1210-24
K-CRHD-1910-24 LED tape	- CRI over 95 - high LED density	20	2.8 W/ft	K-CRHD27-1910-24 K-CRHD35-1910-24 K-CRHD40-1910-24
K-CR-1220-24 LED tape	- CRI over 95	20	2.9 W/ft	K-CR22-1220-24 K-CR25-1220-24 K-CR27-1220-24 K-CR30-1220-24 K-CR35-1220-24 K-CR40-1220-24 K-CR50-1220-24
K-CR-1275-24 LED tape	- CRI over 95	20	4.4 W/ft	K-CR22-1275-24 K-CR25-1275-24 K-CR27-1275-24 K-CR30-1275-24 K-CR35-1275-24 K-CR40-1275-24 K-CR50-1275-24
K-HEHD-1440-24-40C LED tape	- High Efficacy - cold weather -40F	20	4.4 W/ft	K-HEHD22-1440-24-40C K-HEHD25-1440-24-40C K-HEHD27-1440-24-40C K-HEHD30-1440-24-40C K-HEHD35-1440-24-40C K-HEHD40-1440-24-40C K-HEHD50-1440-24-40C
K-CRHD-1820-24 LED tape	- CRI over 95 - high LED density	20	5.6 W/ft	K-CRHD27-1820-24
KWP-CR-1220-24 LED tape	- CRI over 95	65	2.9 W/ft	KWP-CR22-1220-24 KWP-CR25-1220-24 KWP-CR27-1220-24 KWP-CR30-1220-24 KWP-CR35-1220-24 KWP-CR40-1220-24 KWP-CR50-1220-24
KWP-CR-1275-24 LED tape	- CRI over 95	65	4.4 W/ft	KWP-CR22-1275-24 KWP-CR25-1275-24 KWP-CR27-1275-24 KWP-CR30-1275-24 KWP-CR35-1275-24 KWP-CR40-1275-24 KWP-CR50-1275-24

TAMI Extrusion
Ref. A05390

RELATED ACCESSORIES > RELATED LED > CRI 90+

NAME	KEY FEATURES	IP PROTECTION RATING	POWER CONSUMPTION	REF.
KWP-GHD-1910-24 LED tape	- high LED density	65	2.8 W/ft	KWP-GHD27-1910-24 KWP-GHD30-1910-24 KWP-GHD35-1910-24 KWP-GHD40-1910-24
KWP-GHD-1640-24 LED tape	- high LED density	65	5 W/ft	KWP-GHD22-1640-24 KWP-GHD25-1640-24 KWP-GHD27-1640-24 KWP-GHD30-1640-24 KWP-GHD35-1640-24 KWP-GHD40-1640-24 KWP-GHD50-1640-24

RELATED ACCESSORIES > RELATED LED > ADJUSTABLE WHITE / DIM TO WARM

NAME	KEY FEATURES	IP PROTECTION RATING	POWER CONSUMPTION	REF.
K-30/18-1770-010V-24V LED tape		20	3.5 W/ft	K-30/18-1770-010V-24V
K-30/18-1770-24V LED tape		20	3.5 W/ft	K-30/18-1770-24
K-SDCR-22T50-1530-24 LED tape	- Tuneable white 2200K-5000K	20	4.7 W/ft	K-SDCR-22T50-1530-24
KWP-SDCR-22T50-1530-24 LED tape	- Tuneable white 2200K-5000K	65	4.7 W/ft	KWP-SDCR-22T50-1530-24
KWP-G22/50-1728-24 LED tape	- Tuneable white 2200K-5000K	65	5.3 W/ft	KWP-G22/50-1728-24