FTPC-S-WP 60~150W voltage (IP66)

Features

- Built-in active PFC function
- Cooling by free air convection
- Isolation class II
- Narrow and low profile
- 100 % full load burn-in test
- Suitable for use in Dry and Damp locations
- Wide operating temperature range (-20°C ~ +45°C)
- Approved for installation directly on wood
- Compliance to worldwide regulations for lighting
- Up to 5 years warranty



Model	Power	Voltage	Current	Protection	Safety & EMC	Working temperature	Dimensions (L×W×H)	Weight
FTPC60V12-S-WP	60W	12V	5.00A	short circuit, overload, over voltage, over temperature	EN61347-1, EN61347-2-13, EN55015, EN61547	-20°C ~ +45°C	339×30×18mm	0.31kg
FTPC60V24-S-WP		24V	2.50A					
FTPC100V12-S-WP	100W	12V	8.33A			-20°C ~ +50°C	356×30×20mm	0.33kg
FTPC100V24-S-WP		24V	4.17A					
FTPC150V12-S-WP	132W	12V	11.00A			-20°C ~ +45°C	356×30×23mm	0.42kg
FTPC150V24-S-WP	150W	24V	6.25A					

FTPC-FP 30~100W voltage (IP44)

Features

- Cooling by free air convection
- Compliance to worldwide safety regulations for lighting
- Compliance to ERP Directive
- Isolation class II
- 100 % full load burn-in test
- Up to 5 years warranty
- Approved for installation directly on wood



Model	Power	Voltage	Current	Protection	Safety & EMC	Working temperature	Dimensions (L×W×H)	Weight
FTPC30V12-FP	30W	12V	2.50A	overload, short circuit, over temperature	EN61347-1, EN61347-2-13, EN55015, EN61547	-20°C ~ +45°C	158×51×17.3mm	0.20kg
FTPC30V24-FP		24V	1.25A					
FTPC60V12-FP	60W	12V	5.00A		EN55015, EN61347-1, EN61347-2-13, EN61547, EN61000-4-2, 3, 4, 5, 6		172×59.5×18.5mm	0.26kg
FTPC60V24-FP		24V	2.50A					
FTPC75V12-FP	75W	12V	6.25A				172×59.5×18.5mm	0.26kg
FTPC75V24-FP		24V	3.13A					
FTPC100V12-FP	100W	12V	8.33A	over current, overload,short circuit, over temperature			167.5×52.8×17.5mm	0.23kg
FTPC100V24-FP		24V	4.17A					