FTPC-D 30~150W voltage (IP20)

Features

- Constant voltage + constand current design
- European AC input range
- 100 % full load burn-in test
- Cooling by free air convection
- AC phase cut (leading or trailing edge) dimmable
- Built-in active PFC function
- Up to 5 years warranty



Model	Power	Voltage	Current	Protection	Safety & EMC	Working temperature	Dimensions (L×W×H)	Weight
FTPC30V12-D	30W	12V	2.50A	short circuit, overload, over voltage, over temperature	EN61347-1, EN61347-2-13, EN55015, EN61547	-20°C ~ +45°C	159×46×18mm	0.20kg
FTPC30V24-D		24V	1.25A					
FTPC50V12-D	50W	12V	4.16A				177×57.8×21.8mm	
FTPC50V24-D		24V	2.08A					
FTPC75V12-D	75W	12V	6.25A				170×56.8×31mm	0.25kg
FTPC75V24-D		24V	3.12A					
FTPC100V12-D	100W	12V	8.33A	short circuit, overload, over temperature	EN 62493, EN61347-1, EN61347-2-13, EN55015, EN61547		200.8×63×30mm	0.45kg
FTPC100V24-D		24V	4.17A					
FTPC150V12-D	150W	12V	11.00A	short circuit, overload, over voltage, over temp.			170×56.5×31mm	0.60kg
FTPC150V24-D		24V	6.25A					



