FTPC-E 8~150W voltage (IP20)

Features

- European AC input range
- Built in active PFC function
- Isolation class II
- Approved for installation directly on wood
- 5 years warranty
- Wide operating temperature range (-20°C ~ +45°C)



Model	Power	Voltage	Current	Protection	Safety & EMC	Working temperature	Dimensions (L×W×H)	Weight
FTPC8V12-E	8W	12V	0.67A	short circuit, overload, over voltage	EN61347-1, EN61347-2-13, EN55015, EN61547	-20°C ~ +45°C	94.5×46.2×19.5mm	0.06kg
FTPC8V24-E		24V	0.33A					
FTPC15V12-E	15W	12V	1.25A				103×35.5×16mm	0.05kg
FTPC15V24-E		24V	0.625A					
FTPC20V12-E	20W	12V	1.67A				103×35.5×16mm	0.06kg
FTPC20V24-E		24V	0.84A					
FTPC30V12-E	30W	12V	2.50A				149×40.4×26.7mm	0.14kg
FTPC30V24-E		24V	1.25A					
FTPC60V12-E	60W	12V	5.00A				170×44.5×28.2mm	0.24kg
FTPC60V24-E		24V	2.50A					
FTPC100V12-E	100W	12V	8.33A	short circuit, overload, over voltage, over temperature			179.4×62.5×30.6mm	0.40kg
FTPC100V24-E		24V	4.17A					
FTPC150V12-E	150W	12V	12.50A				179.4×62.5×30.6mm	0.42kg
FTPC150V24-E		24V	6.25A					

