FTPC-L 20~150W voltage (IP20)

Features

- Wide operating temperature range (-20°C ~ +45°C)
- Isolation class II
- Compilance to ERP directive
- Lifetime 50 000hrs



Model	Power	Voltage	Current	Protection	Safety & EMC	Working temperature	Dimensions (L×W×H)
FTPC20V12-L	20W	12V	1.67A	open circuit, short circuit, overload, over temperature	IEC61347-1, IEC61347-2-13, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62493	-20°C ~ +45°C	123×44.6×19.2mm
FTPC20V24-L		24V	0.83A				
FTPC30V12-L	30W	12V	2.50A				123×44.6×19.2mm
FTPC30V24-L		24V	1.25A				
FTPC40V12-L	40W	12V	3.33A				149×40.4×26.7mm
FTPC40V24-L		24V	1.67A				
FTPC50V12-L	50W	12V	4.16A				149×40.4×26.7mm
FTPC50V24-L		24V	2.08A				
FTPC60V12-L	60W	12V	5.00A				170×44.5×28.2mm
FTPC60V24-L		24V	2.50A				
FTPC75V12-L	75W	12V	6.25A				170×44.5×28.2mm
FTPC75V24-L		24V	3.125A				
FTPC100V12-L	100W	12V	7.50A				170×44.5×28.2mm
FTPC100V24-L		24V	4.17A				
FTPC150V12-L	150W	12V	11.00A				179×624.5×30.6mm
FTPC150V24-L		24V	6.25A				

