FTPC-C 30~150W voltage (IP20)

Features

- Built-in active PFC function (30W~150W)
- Cooling by free air convection
- Compliance to worldwide safety regulations for lighting
- 100 % full load burn-in test
- Isolation class II
- Wide operating temperature range (-20°C ~ +45°C)
- Approved for installation directly on wood
- Up to 5 years warranty



Model	Power	Voltage	Current	Protection	Safety & EMC	Working temperature	Dimensions (L×W×H)	Weight
FTPC30V12-C	30W	12V	2.50A	short circuit, over current	EN61347-1, EN61347-2-13, EN55015, EN55024, EN61547, EN61000-4-2, -3, -4, -5, -6, -8, -11	-20°C ÷ +45°C	156×50×17mm	0.15kg
FTPC30V24-C		24V	1.25A					
FTPC50V12-C	50W	12V	4.20A	short circuit, over current, overload, over temperature			160×58×18mm	0.16kg
FTPC50V24-C		24V	2.08A					
FTPC75V12-C	70W	12V	5.83A	short circuit, over current, overload, over temperature	EN 61347-1, EN 61347-2-13, EN 62493, EN 55015, EN 61547, EN 61000-3-3; EN 61000-3-2		170×44.5×28.2mm	0.25kg
FTPC75V24-C	75W	24V	3.13A					
FTPC100V12-C	100W	12V	8.33A	short circuit, overload, over temperature			180×65.5×31.2mm	0.45kg
FTPC100V24-C		24V	4.16A					
FTPC150V12-C	132W	12V	11.00A	short circuit, overload, over temperature	EN 61347-1, EN 61347-2-13, EN 55015, EN 61547		177×56.4×17.2mm	0.27kg
FTPC150V24-C	150W	24V	6.25A					