
LUMINAIRE PHOTOMETRIC TEST REPORT

Report number:

MANUFACTURER: Lamppukauppa Led Store Oy		
ADDRESS: Mesikukantie 16, 01300 VANTAA | www.ledstore.fi		
NAME: LED FOKUS SURFACE - color temperature adjustable, dimmable, 16W, CRI98, IP20	SKU: FOKUS-SURFACE	TYPE: LED
SPECIFICATION: LED light, measured from single beam at the warm end of color range, with beam angle set to 37	NOTES: Color temperature adjustable	MEASURED BY: Lamppukauppa Led Store Oy

DATA OF LAMP		Imax(cd)	1026	S/MH(C0/180)	0.53
MODEL		EFFICIENCY(%)	100.0	S/MH(C90/270)	0.53
NOMINAL POWER(W)	7	TOTAL FLUX(lm)	388.48	Voltage(V)	230.0
RATED VOLTAGE(V)	220.0	EFFICIENCY(lm/W)	48.3	Current(A)	0.035
NOMINAL FLUX(lm)	388.5	η up(%)	0.0	Power(W)	8.050
LAMPS QUANTITY	1	η down(%)	100.0	Power Factor(PF)	1.000
TEST VOLTAGE(V)	230.0	Effictive Flux(lm)	334.1	EEI	0.248(B)

LUMINOUS INTENSITY DISTRIBUTION



AVERAGE BEAM ANGLE(45%):37.0 DEG


Test System:HopooColor HP880
Temperature:25.3DEG
Operators:
Test Date:09-20-2024

Test Set: 5.0deg/s C-Gamma (TYPE C)
Humidity:65.0%
Test Distance:1.000 m
Remarks:

Spectrum Chart

Report number:

MANUFACTURER: Lamppukauppa Led Store Oy		
ADDRESS: Mesikukantie 16, 01300 VANTAA | www.ledstore.fi		
NAME: LED FOKUS SURFACE - color temperature adjustable, dimmable, 16W, CRI98, IP20	SKU: FOKUS-SURFACE	TYPE: LED
SPECIFICATION: LED light, measured from single beam at the warm end of color range, with beam angle set to 37	NOTES: Color temperature adjustable	MEASURED BY: Lamppukauppa Led Store Oy



Avg Chro. Para.

CCT: 2590K Chro. Coor.: xa=0.4672 ya=0.4093 u'a=0.2679 v'a=0.5280 ¦¤u'v'=0.0008

Current Angle: C=0.0¡ã G=0.0¡ã

Chroma Parameters

Chro.Coor.: x=0.4685 y=0.4108 u'=0.2680 v'=0.5287 duv=-0.0005

CCT: 2585K Dominant Wave: 585.0nm Purity: 63.9% Light Intensity: 4988.3cd

Flux RGB Ratio: R=60.7%,G=30.7%,B=8.7% Peak Wave: 636.8nm Half Width: 137.5nm

Rendering Index: Ra= 96.1

R1 =96	R2 =97	R3 =99	R4 =96	R5 =96	R6 =93	R7 =96	R8 =96
R9 =94	R10=94	R11=92	R12=87	R13=96	R14=99	R15=99	

Instrument State


Scan Range: 380nm-780nmIntegral Time: 24.0ms Peak Signal: 24000 Dark Signal: 54941

Test System:HopooColor HP880 Test Set: 5.0deg/s C-Gamma (TYPE C)
Temperature:25.3DEG Humidity:65.0%
Operators: Test Distance:1.000 m
Test Date:09-20-2024 Remarks:

AVERAGE AND CENTER E Figure

Report number:

MANUFACTURER: Lamppukauppa Led Store Oy		
ADDRESS: Mesikukantie 16, 01300 VANTAA | www.ledstore.fi		
NAME: LED FOKUS SURFACE - color temperature adjustable, dimmable, 16W, CRI98, IP20	SKU: FOKUS-SURFACE	TYPE: LED
SPECIFICATION: LED light, measured from single beam at the warm end of color range, with beam angle set to 37	NOTES: Color temperature adjustable	MEASURED BY: Lamppukauppa Led Store Oy



Angle:37.0deg


Test System:HopooColor HP880
Temperature:25.3DEG
Operators:
Test Date:09-20-2024

Test Set: 5.0deg/s C-Gamma (TYPE C)
Humidity:65.0%
Test Distance:1.000 m
Remarks:

ISOCANDELA DIAGRAM

Report number:

MANUFACTURER: Lamppukauppa Led Store Oy		
ADDRESS: Mesikukantie 16, 01300 VANTAA | www.ledstore.fi		
NAME: LED FOKUS SURFACE - color temperature adjustable, dimmable, 16W, CRI98, IP20	SKU: FOKUS-SURFACE	TYPE: LED
SPECIFICATION: LED light, measured from single beam at the warm end of color range, with beam angle set to 37	NOTES: Color temperature adjustable	MEASURED BY: Lamppukauppa Led Store Oy



Test System:HopooColor HP880
Temperature:25.3DEG
Operators:
Test Date:09-20-2024

Test Set: 5.0deg/s C-Gamma (TYPE C)
Humidity:65.0%
Test Distance:1.000 m
Remarks: