
LUMINAIRE PHOTOMETRIC TEST REPORT

Report number:

MANUFACTURER: Lamppukauppa Led Store Oy		
ADDRESS: Mesikukantie 16, 01300 VANTAA | www.ledstore.fi		
NAME: LED PANEL 120x120, TUNNELMA, colour temperature adjustable, dimmable, 6W, CRI98, IP54	SKU: PANEL120-CCT	TYPE: LED
SPECIFICATION: LED panel, measured at the cool end of the color temperature range	NOTES: Color temperature adjustable	MEASURED BY: Lamppukauppa Led Store Oy

DATA OF LAMP		Imax(cd)	161.4	S/MH(C0/180)	1.28
MODEL		EFFICIENCY(%)	100.0	S/MH(C90/270)	1.28
NOMINAL POWER(W)	6	TOTAL FLUX(lm)	494.92	Voltage(V)	24.00
RATED VOLTAGE(V)	220.0	EFFICIENCY(lm/W)	76.4	Current(A)	0.270
NOMINAL FLUX(lm)	494.9	η up(%)	0.0	Power(W)	6.480
LAMPS QUANTITY	1	η down(%)	100.0	Power Factor(PF)	1.000
TEST VOLTAGE(V)	24.0	Effictive Flux(lm)	488.1	EEI	0.149(A+)

LUMINOUS INTENSITY DISTRIBUTION



AVERAGE BEAM ANGLE(45%):124.0 DEG


Test System:HopooColor HP880
Temperature:25.3DEG
Operators:
Test Date:09-20-2024


Test Set: 5.0deg/s C-Gamma (TYPE C)
Humidity:65.0%
Test Distance:1.000 m
Remarks:

Spectrum Chart

Report number:

MANUFACTURER: Lamppukauppa Led Store Oy		
ADDRESS: Mesikukantie 16, 01300 VANTAA | www.ledstore.fi		
NAME: LED PANEL 120x120, TUNNELMA, colour temperature adjustable, dimmable, 6W, CRI98, IP54	SKU: PANEL120-CCT	TYPE: LED
SPECIFICATION: LED panel, measured at the cool end of the color temperature range	NOTES: Color temperature adjustable	MEASURED BY: Lamppukauppa Led Store Oy





Avg Chro. Para.

CCT: 5236K Chro. Coor.: xa=0.3394 ya=0.3573 u'a=0.2054 v'a=0.4866 ¦¤u'v'=0.0000

Current Angle: C=0.0¡ã G=0.0¡ã

Chroma Parameters

Chro.Coor.: x=0.3394 y=0.3573 u'=0.2054 v'=0.4866 duv=0.0052

CCT: 5235K Dominant Wave: 563.8nm Purity: 9.1% Light Intensity: 516.8cd

Flux RGB Ratio: R=34.5%,G=39.4%,B=26.1% Peak Wave: 446.6nm Half Width: 20.1nm

Rendering Index: Ra= 98.5

R1 =100	R2 =99	R3 =99	R4 =96	R5 =99	R6 =99	R7 =99	R8 =97
R9 =92	R10=99	R11=93	R12=91	R13=99	R14=99	R15=98	

Instrument State


Scan Range: 380nm-780nmIntegral Time: 200.0ms Peak Signal: 200000 Dark Signal: 54438

Test System:HopooColor HP880 Test Set: 5.0deg/s C-Gamma (TYPE C)
Temperature:25.3DEG Humidity:65.0%
Operators: Test Distance:1.000 m
Test Date:09-20-2024 Remarks:

AVERAGE AND CENTER E Figure

Report number:

MANUFACTURER: Lamppukauppa Led Store Oy		
ADDRESS: Mesikukantie 16, 01300 VANTAA | www.ledstore.fi		
NAME: LED PANEL 120x120, TUNNELMA, colour temperature adjustable, dimmable, 6W, CRI98, IP54	SKU: PANEL120-CCT	TYPE: LED
SPECIFICATION: LED panel, measured at the cool end of the color temperature range	NOTES: Color temperature adjustable	MEASURED BY: Lamppukauppa Led Store Oy



Angle:123.9deg


Test System:HopooColor HP880
Temperature:25.3DEG
Operators:
Test Date:09-20-2024

Test Set: 5.0deg/s C-Gamma (TYPE C)
Humidity:65.0%
Test Distance:1.000 m
Remarks:

ISOCANDELA DIAGRAM

Report number:

MANUFACTURER: Lamppukauppa Led Store Oy		
ADDRESS: Mesikukantie 16, 01300 VANTAA | www.ledstore.fi		
NAME: LED PANEL 120x120, TUNNELMA, colour temperature adjustable, dimmable, 6W, CRI98, IP54	SKU: PANEL120-CCT	TYPE: LED
SPECIFICATION: LED panel, measured at the cool end of the color temperature range	NOTES: Color temperature adjustable	MEASURED BY: Lamppukauppa Led Store Oy



Test System:HopooColor HP880
Temperature:25.3DEG
Operators:
Test Date:09-20-2024

Test Set: 5.0deg/s C-Gamma (TYPE C)
Humidity:65.0%
Test Distance:1.000 m
Remarks: