
LUMINAIRE PHOTOMETRIC TEST REPORT

Report number:

MANUFACTURER: Lamppukauppa Led Store Oy		
ADDRESS: Mesikukantie 16, 01300 VANTAA | www.ledstore.fi		
NAME: LED PANEL 600x1200, TUNNELMA, colour temperature adjustable, dimmable, 55W, CRI97, IP54	SKU: Panel600x1200-CCT-2,0	TYPE: LED
SPECIFICATION: LED panel, measured at the warm end of the color temperature range	NOTES: Color temperature adjustable	MEASURED BY: Lamppukauppa Led Store Oy

DATA OF LAMP		Imax(cd)	336.9	S/MH(C0/180)	1.53
MODEL		EFFICIENCY(%)	100.0	S/MH(C90/270)	1.53
NOMINAL POWER(W)	70	TOTAL FLUX(lm)	1360.0	Voltage(V)	24.00
RATED VOLTAGE(V)	220.0	EFFICIENCY(lm/W)	23.9	Current(A)	2.370
NOMINAL FLUX(lm)	1360.1	η up(%)	0.0	Power(W)	56.87
LAMPS QUANTITY	1	η down(%)	100.0	Power Factor(PF)	1.000
TEST VOLTAGE(V)	24.0	Effictive Flux(lm)	1358.4	EEI	0.570(B)

LUMINOUS INTENSITY DISTRIBUTION



AVERAGE BEAM ANGLE(45%):148.1 DEG


Test System:HopooColor HP880
Temperature:25.3DEG
Operators:
Test Date:09-20-2024

Test Set: 5.0deg/s C-Gamma (TYPE C)
Humidity:65.0%
Test Distance:1.000 m
Remarks:

Spectrum Chart

Report number:

MANUFACTURER: Lamppukauppa Led Store Oy		
ADDRESS: Mesikukantie 16, 01300 VANTAA | www.ledstore.fi		
NAME: LED PANEL 600x1200, TUNNELMA, colour temperature adjustable, dimmable, 55W, CRI97, IP54	SKU: Panel600x1200-CCT-2,0	TYPE: LED
SPECIFICATION: LED panel, measured at the warm end of the color temperature range	NOTES: Color temperature adjustable	MEASURED BY: Lamppukauppa Led Store Oy



Avg Chro. Para.

CCT: 2863K Chro. Coor.: xa=0.4554 ya=0.4235 u'a=0.2540 v'a=0.5315 ¦¤u'v'=0.0001

Current Angle: C=0.0¡ã G=0.0¡ã

Chroma Parameters

Chro.Coor.: x=0.4555 y=0.4236 u'=0.2540 v'=0.5315 duv=0.0052

CCT: 2861K Dominant Wave: 581.8nm Purity: 63.9% Light Intensity: 809.7cd

Flux RGB Ratio: R=56.4%,G=34.2%,B=9.4% Peak Wave: 636.8nm Half Width: 160.1nm

Rendering Index: Ra= 96.8

R1 =98	R2 =98	R3 =97	R4 =95	R5 =97	R6 =98	R7 =96	R8 =97
R9 =96	R10=97	R11=93	R12=87	R13=98	R14=98	R15=97	

Instrument State


Scan Range: 380nm-780nmIntegral Time: 160.0ms Peak Signal: 160000 Dark Signal: 55585

Test System:HopooColor HP880	Test Set: 5.0deg/s C-Gamma (TYPE C)
Temperature:25.3DEG	Humidity:65.0%
Operators:	Test Distance:1.000 m
Test Date:09-20-2024	Remarks:

AVERAGE AND CENTER E Figure

Report number:

MANUFACTURER: Lamppukauppa Led Store Oy		
ADDRESS: Mesikukantie 16, 01300 VANTAA | www.ledstore.fi		
NAME: LED PANEL 600x1200, TUNNELMA, colour temperature adjustable, dimmable, 55W, CRI97, IP54	SKU: Panel600x1200-CCT-2,0	TYPE: LED
SPECIFICATION: LED panel, measured at the warm end of the color temperature range	NOTES: Color temperature adjustable	MEASURED BY: Lamppukauppa Led Store Oy



Angle:139.9deg


Test System:HopooColor HP880
Temperature:25.3DEG
Operators:
Test Date:09-20-2024

Test Set: 5.0deg/s C-Gamma (TYPE C)
Humidity:65.0%
Test Distance:1.000 m
Remarks:

ISOCANDELA DIAGRAM

Report number:

MANUFACTURER: Lamppukauppa Led Store Oy		
ADDRESS: Mesikukantie 16, 01300 VANTAA | www.ledstore.fi		
NAME: LED PANEL 600x1200, TUNNELMA, colour temperature adjustable, dimmable, 55W, CRI97, IP54	SKU: Panel600x1200-CCT-2,0	TYPE: LED
SPECIFICATION: LED panel, measured at the warm end of the color temperature range	NOTES: Color temperature adjustable	MEASURED BY: Lamppukauppa Led Store Oy



Test System:HopooColor HP880
Temperature:25.3DEG
Operators:
Test Date:09-20-2024

Test Set: 5.0deg/s C-Gamma (TYPE C)
Humidity:65.0%
Test Distance:1.000 m
Remarks: